

**ABC MULTIPURPOSE  
PORTABLE  
STORED PRESSURE FIRE EXTINGUISHERS**



- **IDEAL USES:** Homes, office buildings, warehouses, farms and woodworking areas.  
(NOTE - Not recommended for use on expensive delicate equipment or computers.)
- **MONOAMMONIUM PHOSPHATE** based dry chemical agent capable of fighting Class "A," "B," and "C" type fires.
- This agent provides the widest and most practical range of extinguisher fire protection coverage.
- Manufactured to ANSI/UL 299 and ANSI/UL 711 Standards.

Specifications	100PSI / 690 kPa Operating Pressure		195PSI / 1340 kPa Operating Pressure					
	2.5 ABC	2.5 ABC V/B	5 ABC	5 ABC V/B	10 ABC TALL	10 ABC SHORT	20 ABC	30 ABC
Part No. Alum Valve	10315	13315	10914	25614	11340	11310	12120	-
Part No. Brass Valve	-	-	10915	25615	11341	-	12121	12905
Capacity lbs/kg	2.5 / 1.13	2.5 / 1.13	5 / 2.27	5 / 2.27	10 / 4.54	10 / 4.54	20 / 9.07	30 / 13.5
U.L. Rating	1A: 10B:C	1A: 10B:C	3A: 40B:C	3A: 40B:C	4A: 80B:C	4A: 80B:C	20A: 120B:C	20A: 150B:C
Ship Wt. Alum Valve	5.25 / 2.38	5.5 / 2.49	9.5 / 4.3	9.75 / 4.4	17.25 / 8.1	17.33 / 8.2	33 / 15.0	-
Ship Wt. Brass Valve	-	-	10 / 4.5	10.3 / 4.7	18.25 / 8.3	-	33.5 / 15.2	52.25 / 23.7
Height ( in / cm )	14.75 / 37.5	14.75 / 37.5	16.25 / 41.6	16.25 / 41.6	21 / 53.3	10.75 / 42.5	21.25 / 53.8	27.25 / 69.4
Width ( in / cm )	4.75 / 12.4	4.75 / 12.4	7.25 / 18.4	7.25 / 18.4	7.33 / 19.7	8.25 / 21.0	8.75 / 22.2	8.75 / 22.2
Diameter ( in / cm )	3.33 / 8.6	3.33 / 8.6	4.25 / 10.8	4.25 / 10.8	5.25 / 13.0	6 / 15.2	7.5 / 19.1	7.5 / 19.1
Bracket	Wall	Veh / Marine	Wall	Veh / Mar	Wall	Wall	Wall	Wall
Range ( Feet/Meters )	9-15/2.7-4.6	9-15/2.7-4.6	12-18/3.7-5.5	12-18/3.7-5.5	15-21/4.6-6.4	15-21/4.6-6.4	15-21/4.6-6.4	25-30/7.6-9.1

Discharge Times sec.	9	9	14	14	22	18	26	32
Cylinder	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel
USCG Approved - Yes	Type B:C Size I		Type A Size II Type B:C Size I		Type A Size II Type B:C Size II		Type A Size II Type B:C Size II	Type A Size II Type B:C Size IV

**PRODUCT DATASHEET LINKS ( PDF )**

Part No. Alum. Valve	<a href="#">10315</a>	<a href="#">13315</a>	<a href="#">10914</a>	<a href="#">25614</a>	<a href="#">11340</a>	<a href="#">11310</a>	<a href="#">12120</a>	--
Part No. Brass Valve	--	--	<a href="#">10915</a>	<a href="#">25615</a>	<a href="#">11341</a>	--	<a href="#">12121</a>	<a href="#">12905</a>

**PURPLE K**



- **POTASSIUM BICARBONATE** based dry chemical agent capable of fighting Class "B" and "C" Type fires.
- The most effective type of dry chemical on Class"B" fires.
- **IDEAL USES:** Garages, service bays, boats, vehicles, fuel storage and transfer areas.
- Manufactured to ANSI/UL 299 and ANSI/UL 711 Standard

Specifications	100PSI / 690 kPa Operating Pressure	195PSI / 1340 kPa Operating Pressure				
Size/Model	2.5 PK V/B	5 PK	5 PK V/B	10 PK TALL	20 PK	30 PK
Part No. Alum Valve	13515	11214	25914	11740	12620	-
Part No. Brass Valve	-	11215	25915	11741	12621	12805
Capacity lbs/kg	2.5 / 1.13	5 / 2.27	5 / 2.27	10 / 4.54	20 / 9.07	30 / 13.6
U.L. Rating	10B:C	20B:C	20B:C	80B:C	120B:C	160B:C
Ship Wt. Alum Valve	5.5 / 2.49	9.5 / 4.3	9.75 / 4.4	17.25 / 8.1	33 / 15.0	-
Ship Wt. Brass Valve	-	10.3 / 4.7	10.3 / 4.7	18.25 / 8.3	33.5 / 15.2	52.25 / 23.7
Height ( in / cm )	14.75 / 37.5	16.25 / 41.6	16.25 / 41.6	21 / 53.3	21.25 / 53.8	27.25 / 69.4
Width ( in / cm )	4.75 / 12.4	7.25 / 18.4	7.25 / 18.4	7.33 / 19.7	8.75 / 22.2	8.75 / 22.2
Diameter ( in / cm )	3.33 / 8.6	4.25 / 10.8	4.25 / 10.8	5.25 / 13.0	7.5 / 19.1	7.5 / 19.1
Bracket	Veh / Marine	Wall	Veh / Mar	Wall	Wall	Wall
Range ( Feet/Meters )	9-15/2.7-4.6	12-18/3.7-5.5	12-18/3.7-5.5	15-21/4.6-6.4	15-21/4.6-6.4	25-30/7.6-9.1
Discharge Times sec.	9	9	9	22	26	32
Cylinder	Steel	Steel	Steel	Steel	Steel	Steel
USCG Approved - Yes	Type B:C Size I	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size III	Type B:C Size IV
<b>PRODUCT DATASHEET LINKS (PDF)</b>						
<b>Part No. Alum. Valve</b>	<b>13515</b>	<b>11214</b>	<b>25914</b>	<b>11740</b>	<b>12620</b>	<b>--</b>
<b>part No. Brass Valve</b>	<b>--</b>	<b>11215</b>	<b>25915</b>	<b>11741</b>	<b>12621</b>	<b>12805</b>

**STANDARD  
STORED PRESSURE  
FIRE EXTINGUISHERS**



- **SODIUM BICARBONATE** based dry chemical agent capable of fighting Class "B" and "C" type fires.
- The original and least expensive type of dry chemical often selected for training programs.
- **IDEAL USES:** Kitchens, garages, vehicles and boats.
- Manufactured to ANSI/UL 299 and ANSI/UL 711 standards.

**PRODUCT DATASHEET LINKS (PDF)**

SPECIFICATIONS	100PSI/690 kPa OPERATING PRESSURE		195PSI/1340 kPa OPERATING PRESSURE			
	2.5 STD V/B	5.5 STD	5.5 STD V/B	10 STD TALL	10 STD SHORT	20 STD
<b>SIZE/MODEL</b>	2.5 STD V/B	5.5 STD	5.5 STD V/B	10 STD TALL	10 STD SHORT	20 STD
<b>Part No. Alum. Valve</b>	13415	11014	13514	11840	11810	12220
<b>Part No. Brass Valve</b>	--	11015	13515	--	--	--
<b>Capacity (lbs/kg)</b>	2.5/1.13	5.5/2.5	5.5/2.5	10/4.54	10/4.54	20/9.07
<b>U.L. Rating</b>	10B:C	40B:C	40B:C	40B:C	40B:C	120B:C
<b>Ship Wt. Alum. Valve (lbs/kg)</b>	5.5/2.49	10/4.5	10.25/4.7	17.75/8.1	17.75/8.1	33/15.0
<b>Ship Wt. Brass Valve (lbs/kg)</b>	--	10.5/4.8	10.75/4.9	18.25/8.3	--	--
<b>Height (in/cm)</b>	14.75/37.5	16 3/8 /41.6	16 3/8 /41.6	21/53.3	16.75/42.5	21 7/16 /53.8
<b>Width (in/cm)</b>	4 7/8 /12.4	7.25/18.4	7.25/18.4	7.75/19.7	8.25/21.0	8.75/22.2
<b>Diameter (in/cm)</b>	3 3/8 /8.6	4.25/10.8	4.25/10.8	5 1/8 /13.0	6/15.2	7.5/19.1
<b>Bracket</b>	Veh/Mar	Wall	Veh/Mar	Wall	Wall	Wall
<b>Range (feet/meter)</b>	9-15/2.7-4.6	12-18/3.7-5.5	12-18/3.7-5.5	15-21/4.6-6.4	15-21/4.6-6.4	15-21/4.6-6.4
<b>Discharge Time (sec.)</b>	9	14	14	14	14	26
<b>Cylinder</b>	Steel	Steel	Steel	Steel	Steel	Steel
<b>USCG Approved - Yes</b>	Type B:C Size I	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size II	Type B:C Size III



## CARBON DIOXIDE STORED PRESSURE FIRE EXTINGUISHERS



- **Carbon Dioxide**, a gaseous agent for class B and C fires.
- **Ideal Uses:** chemical and manufacturing plants, oil rigs, rail yards, warehouses, construction sites, parking garages, airport ramps, boat docks and large laboratories.
- Manufactured to ANSI/UL 154 and ANSI/UL 711 standards.

<b>SPECIFICATIONS</b>	<b>PORTABLE UNITS</b>			
SIZE/MODEL	5CD	10CD	15CD	20CD
PART NO.	45100	45600	46100	46600
VALVE	CHROME PLATED BRASS			
CAPACITY lbs./kg)	5 • 2.27	10 • 4.54	15 • 6.80	20 • 9.07
U.L. Rating	5B:C	10B:C	10B:C	10B:C
Cylinder	ALUMINUM			
Ship wt. (lbs./kg)	13 <sup>3</sup> / <sub>4</sub> • 6.3	27 <sup>3</sup> / <sub>4</sub> • 12.6	37 <sup>3</sup> / <sub>4</sub> • 17.1	49 • 22.2
Height (in./cm)	17 <sup>3</sup> / <sub>8</sub> • 44.1	19 <sup>3</sup> / <sub>4</sub> • 50.2	26 <sup>3</sup> / <sub>8</sub> • 67.0	26 <sup>7</sup> / <sub>8</sub> • 68.2
Width (in./cm)	8 <sup>1</sup> / <sub>4</sub> • 21.0	12 • 30.5	12 • 30.5	13 • 33.0
Diameter (in./cm)	5 <sup>1</sup> / <sub>4</sub> • 13.3	6 <sup>15</sup> / <sub>16</sub> • 17.6	6 <sup>7</sup> / <sub>8</sub> • 17.5	8 • 20.3
Bracket	Wall	Wall	Wall	Wall
Range (feet/meters)	4-8/1.2-2.4	4-8/1.2-2.4	4-8/1.2-2.4	4-8/1.2-2.4
Discharge time (seconds)	8	10	15	20
USCG Approved	Type B:C Size I		Type B:C Size II	

**PRODUCT DATASHEET LINKS ( PDF )**

Part No.	<a href="#">45100</a>	<a href="#">45600</a>	<a href="#">46100</a>	<a href="#">46600</a>
----------	-----------------------	-----------------------	-----------------------	-----------------------

## Halotron™ I



- **Halotron™**, a HydroChloroFluoro Carbon nonconductive agent pressurized with Argon. Approved by the EPA and FAA as HCFC blend B for use on class "A", "B" and "C" type fires.
- This is an excellent replacement for Halon 1211.
- **IDEAL USES:** Computers, telephone switch gears, sensitive data storage areas, offices, boats, forest machines, aircraft flight lines, and mobile units.
- Manufactured to ANSI/UL 2129 and ANSI/UL 711 standards.

SPECIFICATIONS	OPERATING PRESSURE – 100PSI/690 kPa									
	2.5F	2.5F V/B	2.5H	2.5H V/B	5F	5F V/B	5H	5H V/B	11	15
Part No. Alum. Valve	70258	70251	70259	70256	70510	70550	75550	75555	71100	71550
Part No. Brass Valve	-	-	-	-	70511	70551	75551	75556	71101	71551
Capacity (lbs./kg)	2½ • 1.13	2½ • 1.13	2½ • 1.13	2½ • 1.13	5 • 2.27	5 • 2.27	5½ • 2.49	5½ • 2.49	11 • 4.99	15½ • 7.03
U.L. Rating	2B:C	2B:C	2B:C	2B:C	5B:C	5B:C	5B:C	5B:C	1A:10B:C	2A:10B:C
Ship Wt. Alum. Valve (lbs./kg)	5¼ • 2.38	5½ • 2.49	5½ • 2.49	5¾ • 2.61	9¼ • 4.2	9½ • 4.3	10 • 4.5	10¼ • 4.7	21¼ • 9.6	25¾ • 11.7
Ship Wt. Brass Valve (lbs./kg)	-	-	-	-	9¼ • 4.4	10 • 4.5	10½ • 4.8	10¼ • 4.9	21¼ • 9.9	26¼ • 11.9
Height (in./cm)	13¾ • 34.0	13¾ • 34.0	13¾ • 34.0	13¾ • 34.0	16¾ • 41.6	16¾ • 41.6	16¾ • 41.6	16¾ • 41.6	17½ • 44.5	17½ • 44.5
Width (in./cm)	5½ • 14.3	5½ • 14.3	6¾ • 17.1	6¾ • 17.1	6¾ • 16.7	7½ • 18.6	6¾ • 16.7	7½ • 18.6	8½ • 21.9	8½ • 21.9
Diameter (in./cm)	3¾ • 8.6	3¾ • 8.6	3¾ • 8.6	3¾ • 8.6	4¼ • 10.8	4¼ • 10.8	4¼ • 10.84	4¼ • 10.8	7 • 17.8	7 • 17.8
Bracket	Wall	V/B	Wall	V/B	Wall	V/B	Wall	V/B	Wall	Wall
Range (feet/meter)	6-10 • 1.8-3	6-10 • 1.8-3	6-10 • 1.8-3	6-10 • 1.8-3	9-15 • 2.7-4.5	9-15 • 2.7-4.5	9-15 • 2.7-4.5	9-15 • 2.7-4.5	9-15 • 2.7-4.5	12-18 • 3.7-5.5
Discharge Times (seconds)	9	9	9	9	9	9	9	9	9	13
Cylinder	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel
USCG Approved	N/A	N/A	N/A	N/A	Type B:C Size I					Type B:C Size II

### PRODUCT DATASHEET LINKS (PDF)

<b>Part No. Alum. Valve</b>	<a href="#">70258</a>	<a href="#">70251</a>	<a href="#">70259</a>	<a href="#">70256</a>	<a href="#">70510</a>	<a href="#">70550</a>	<a href="#">75550</a>	<a href="#">75555</a>	<a href="#">71100</a>	<a href="#">71550</a>
<b>Part No. Brass Valve</b>	--	--	--	--	<a href="#">70511</a>	<a href="#">70551</a>	<a href="#">75551</a>	<a href="#">75556</a>	<a href="#">71101</a>	<a href="#">71551</a>

## WET CHEMICAL COOKING APPLIANCE STORED PRESSURE

[\(Download PDF\)](#)

- **WET CHEMICAL** Extinguishers contain a blend of Potassium Acetate and Citrate that is extremely effective in combating fires in today's cooking appliances that use unsaturated cooking oils. This chemical excels in effectively fighting and cooling these very hot and difficult fires. The application of the agent provides a fine mist spray that prevents splashing of the grease and confines it to the cooking surface.
- **Manufactured to ANSI/UL 8 AND ANSI/UL 711 Standards**  
Designed to work in conjunction with pre-engineered hood systems. Tested to extinguish one 18" x 24" fat fryer.

SPECIFICATIONS	WET CHEMICAL
100 PSI / 690 kPa	OPERATING PRESSURE
Part Number	50006 ( <a href="#">Datasheet</a> )
Application	Hose
Model Number	WC-6 Liter
U.L. Rating	1A:K
Capacity (gal/liters)	1.59 / 6
Shipping Weight (lbs/kg)	22 / 10
Extinguisher Height (in/cm)	19.25 / 48.9
Height w/Hose Installed (in/cm)	25.5 / 64.8
Width w/Hose Installed (in/cm)	11 / 27.9
Cylinder diameter (in/cm)	7 / 17.8
Discharge Time (seconds)	54
Standard Bracket	Wall
Cylinder	Stainless Steel
Temperature range	+40°F to +120°F
USCG Approved	No



**6 LITER WET CHEMICAL FIRE  
EXTINGUISHER**

<b>WATER</b>
--------------

- **WATER**, a liquid agent only recommended for fighting Class "A" type fires in hand portable extinguishers.
- **IDEAL USES:**  
Schools, Theaters, Department and Retail Store Rooms.
- **Manufactured to ANSI/UL8 and ANSI/UL711 Standards**

SPECIFICATIONS	WATER
100 PSI / 690 kPa	OPERATING PRESSURE
Part Number	50000 ( <a href="#">DATASHEET</a> )PDF
Model	500
Capacity (gal/liters)	2.5 /9.5
Valve Chrome Plated	Brass
Cylinder	S/S
U.L. Rating	2A
Ship Wt. (lbs/kg)	7.75 /3.5
Height (in/cm)	24.5 / 62.2
Width (in/cm)	9 / 22.9
Cylinder Diameter (in/cm)	7 /17.8
Temperature range	+40°F to +120°F
Bracket	Wall
USCG Approved	No



**2 1/2 GALLON WATER FIRE  
EXTINGUISHER**