

**PURPLE K**



- **POTASSIUM BICARBONATE** based dry chemical agent capable of fighting Class "B" and "C" Type fires.
- The most effective type of dry chemical on Class"B" fires.
- **IDEAL USES:** Garages, service bays, boats, vehicles, fuel storage and transfer areas.
- Manufactured to ANSI/UL 299 and ANSI/UL 711 Standard

Specifications	100PSI / 690 kPa Operating Pressure	195PSI / 1340 kPa Operating Pressure				
Size/Model	2.5 PK V/B	5 PK	5 PK V/B	10 PK TALL	20 PK	30 PK
Part No. Alum Valve	13515	11214	25914	11740	12620	-
Part No. Brass Valve	-	11215	25915	11741	12621	12805
Capacity lbs/kg	2.5 / 1.13	5 / 2.27	5 / 2.27	10 / 4.54	20 / 9.07	30 / 13.6
U.L. Rating	10B:C	20B:C	20B:C	80B:C	120B:C	160B:C
Ship Wt. Alum Valve	5.5 / 2.49	9.5 / 4.3	9.75 / 4.4	17.25 / 8.1	33 / 15.0	-
Ship Wt. Brass Valve	-	10.3 / 4.7	10.3 / 4.7	18.25 / 8.3	33.5 / 15.2	52.25 / 23.7
Height ( in / cm )	14.75 / 37.5	16.25 / 41.6	16.25 / 41.6	21 / 53.3	21.25 / 53.8	27.25 / 69.4
Width ( in / cm )	4.75 / 12.4	7.25 / 18.4	7.25 / 18.4	7.33 / 19.7	8.75 / 22.2	8.75 / 22.2
Diameter ( in / cm )	3.33 / 8.6	4.25 / 10.8	4.25 / 10.8	5.25 / 13.0	7.5 / 19.1	7.5 / 19.1
Bracket	Veh / Marine	Wall	Veh / Mar	Wall	Wall	Wall
Range ( Feet/Meters )	9-15/2.7-4.6	12-18/3.7-5.5	12-18/3.7-5.5	15-21/4.6-6.4	15-21/4.6-6.4	25-30/7.6-9.1
Discharge Times sec.	9	9	9	22	26	32
Cylinder	Steel	Steel	Steel	Steel	Steel	Steel
USCG Approved - Yes	Type B:C Size I	Type B:C Size I	IType B:C Size II	Type B:C Size III	Type B:C Size IV	
<b>PRODUCT DATASHEET LINKS (PDF)</b>						
<b>Part No. Alum. Valve</b>	<b>13515</b>	<b>11214</b>	<b>25914</b>	<b>11740</b>	<b>12620</b>	<b>--</b>
<b>part No. Brass Valve</b>	<b>--</b>	<b>11215</b>	<b>25915</b>	<b>11741</b>	<b>12621</b>	<b>12805</b>