

**STANDARD
STORED PRESSURE
FIRE EXTINGUISHERS**



- **SODIUM BICARBONATE** based dry chemical agent capable of fighting Class "B" and "C" type fires.
- The original and least expensive type of dry chemical often selected for training programs.
- **IDEAL USES:** Kitchens, garages, vehicles and boats.
- Manufactured to ANSI/UL 299 and ANSI/UL 711 standards.

PRODUCT DATASHEET LINKS (PDF)

SPECIFICATIONS	100PSI/690 kPa OPERATING PRESSURE	195PSI/1340 kPa OPERATING PRESSURE				
	2.5 STD V/B	5.5 STD	5.5 STD V/B	10 STD TALL	10 STD SHORT	20 STD
SIZE/MODEL	2.5 STD V/B	5.5 STD	5.5 STD V/B	10 STD TALL	10 STD SHORT	20 STD
Part No. Alum. Valve	13415	11014	13514	11840	11810	12220
Part No. Brass Valve	--	11015	13515	--	--	--
Capacity (lbs/kg)	2.5/1.13	5.5/2.5	5.5/2.5	10/4.54	10/4.54	20/9.07
U.L. Rating	10B:C	40B:C	40B:C	40B:C	40B:C	120B:C
Ship Wt. Alum. Valve (lbs/kg)	5.5/2.49	10/4.5	10.25/4.7	17.75/8.1	17.75/8.1	33/15.0
Ship Wt. Brass Valve (lbs/kg)	--	10.5/4.8	10.75/4.9	18.25/8.3	--	--
Height (in/cm)	14.75/37.5	16 3/8 /41.6	16 3/8 /41.6	21/53.3	16.75/42.5	21 7/16 /53.8
Width (in/cm)	4 7/8 /12.4	7.25/18.4	7.25/18.4	7.75/19.7	8.25/21.0	8.75/22.2
Diameter (in/cm)	3 3/8 /8.6	4.25/10.8	4.25/10.8	5 1/8 /13.0	6/15.2	7.5/19.1
Bracket	Veh/Mar	Wall	Veh/Mar	Wall	Wall	Wall
Range (feet/meter)	9-15/2.7-4.6	12-18/3.7-5.5	12-18/3.7-5.5	15-21/4.6-6.4	15-21/4.6-6.4	15-21/4.6-6.4
Discharge Time (sec.)	9	14	14	14	14	26
Cylinder	Steel	Steel	Steel	Steel	Steel	Steel
USCG Approved - Yes	Type B:C Size I	Type B:C Size I	Type B:C Size I	Type B:C Size II	Type B:C Size II	Type B:C Size III

